

Tvheadend - Feature #4157

Option to add SAT->IP by IP address

2017-01-02 10:42 - Josu Lazkano

Status:	Rejected	Start date:	2017-01-02
Priority:	Normal	Due date:	
Assignee:		% Done:	0%
Category:	SAT>IP	Estimated time:	0.00 hour
Target version:			
Description			
Hello,			
I have a SAT->IP server (minisatip) in other network than Tvheadend server, so it can not search with broadcast messages.			
Could be possible to add a option to add a specific SAT->IP server? With IP or FQDN.			
This is asked before in the fórum: https://tvheadend.org/boards/5/topics/23685			
Regards.			

History

#1 - 2017-01-02 11:15 - Mono Polimorph

Hi,

As several "discovery" protocols have troubles (multicat blocking, non-routable, etc.), I recommend to add MANUAL DISCOVERY support to all client protocols, like SAT>IP and HDHRROMERUN. For the developer it's easy, as any discovery protocol executes some action and returns the list of devices. So, the implementation is quite simple: in the list of discovered devices add the option for "user defined addresses". No more, no less!

I hope this will be implemented!

#2 - 2017-01-02 17:45 - Jaroslav Kysela

- Status changed from New to Rejected

It's already resolved for the SAT>IP server in tvh (--satip_xml option).

#3 - 2017-01-03 14:51 - Josu Lazkano

Jaroslav Kysela wrote:

It's already resolved for the SAT>IP server in tvh (--satip_xml option).

Hello,

So how could I add my SAT->IP server channels? I got it in other network, but it is reachable from Tvheadend.

It is possible to add a Network option for SAT->IP?

Best regards.

#4 - 2017-01-03 18:51 - Jaroslav Kysela

You must know the URL with the SAT>IP description - XML contents. It's broadcasted in UPnP discovery multicast. For minisatip it's:

<http://HOST:8080/desc.xml>

TVH will create a new SAT>IP tuner (client) with this option.

Also, the SAT>IP protocol uses UDP data transfers - so if you are behind firewall, use the RTP/AVP/TCP transfer mode (in the tvheadend SAT>IP tuner settings).

#5 - 2017-01-03 19:58 - Josu Lazkano

Jaroslav Kysela wrote:

You must know the URL with the SAT>IP description - XML contents. It's broadcasted in UPnP discovery multicast. For minisatip it's:

[...]

TVH will create a new SAT>IP tuner (client) with this option.

Also, the SAT>IP protocol uses UDP data transfers - so if you are behind firewall, use the RTP/AVP/TCP transfer mode (in the tvheadend SAT>IP tuner settings).

Thanks Jaroslav,

Sorry for all my newby questions, but where could I add the "http://HOST:8080/desc.xml"?

I have no firewall between minisatip and tvheadend.

Best regards.